




Optical Fiber Fast Connector

		
SC /PC	SC/APC	LC /PC

Introduction

TS-FC Series Optical Fiber Fast Connector take use of the United States based on innovative plastic 1000/1000 material compared to other manufacturers of material more quality, embedded a 60mm embedded fiber (grinding) to ensure the length of the uniform, but also to ensure the length of the cut fiber. The stability of the insertion and return loss is ensured by using the 1 core of the concentric degree. When assembled, the FIS index of the United States was added to the match, and the temperature range was wide. The oil separation rate was zero, and it had good oxidation resistance and long-term stability. Can be customized according to customer demand for different types of products.

Application

- FTTH fiber optic terminal for the opening
- Connection box, cabinet, box, etc.
- Recovery and maintenance of accidents such as broken fiber
- Local area network, wide area network, data and video transmission
- Construction and maintenance of terminal user optical fiber access
- Optical fiber access for mobile base station

Technical Parameters

Item	Technical Parameters
Optical Fiber Diameter	125 um (657A & 657B)
Tight Buffer Diameter	250um
Fiber Mode	Single Mode, Multi Mode
Connector Type	SC (UPC or APC) LC(UPC or APC)
Operation Time	100s (No Fiber Cut)
Insert Loss	≤0.5dB (1310nm & 1550nm)
Return Loss	≤-50dB
Fastening Strength of Naked Fiber	>5 N
Fastening Strength of Naked Fiber Holder	>10 N
Tensile Strength	>20 N
Using Temperature	-40 ~ +85℃
Online Tensile Strength (20 N)	IL ≤ 0.5dB RL ≤5dB
Mechanical Durability (500 Times)	IL ≤ 0.5dB RL ≤5dB
Drop-off Test(Drop-off height 4m, once per direction, totally 3 times)	IL ≤ 0.5dB RL ≤5dB
Atmospheric pressure requirements	62kPa~106kPa
Relative humidity requirement	≤95% (+30℃)
Fast Connector Length	60mm/53.5mm/38mm

Notice:

TONGSION reserves the right to make changes to or discontinue any optical link product or service identified in this publication, without notice, in order to improve design and/or performance. Applications that are described herein for any of the optical link products are for illustrative purposes only. TONGSION makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Contact:

E-mail:sales@tongsion.com

<http://www.tongsion.com>